

January 2015

# Mycronic SMD Tower™ 2000 Specification

---



**MYCRONIC**  
When passion meets innovation ●

# Specification Mycronic SMD Tower 2000

## CAPABILITY

RANDOM ACCESS STORAGE SYSTEM FOR SMD REELS	
Reel sizes	8 to 24 mm (4/100 mm reels) 8 to 24 mm (7/180 mm reels) 8 to 56 mm (13/330 mm reels)
Freely configurable and expandable	
Access time	5 reels/minutes typ.

## CAPACITY

CASSETTE CAPACITY	
CASSETTE TYPE	NUMBER
4" - 7"	30
13"	17

MAXIMUM REEL CAPACITY				
REEL WIDTH	CASSETTES / SMD TOWER	REELS / CASSETTE	NUMBER OF REELS	TOTAL
8 mm / 4" - 7"	30	14	420	658
8 mm / 13"	17	14	238	

MAXIMUM TRAY CAPACITY				
CASSETTE WIDTH	CASSETTES / SMD TOWER	TRAY BOXES / CASSETTE	NUMBER OF TRAY BOXES	TOTAL
44 mm / 13"	17	5	85	425

STANDARD CONFIGURATION				
REEL WIDTH	CASSETTES / SMD TOWER	REELS / CASSETTE	NUMBER OF REELS	TOTAL
8 mm / 4" - 7"	21	14	294	562
8 mm / 13"	5	14	70	
12 mm / 4" - 7"	3	12	36	
12 mm / 13"	3	12	36	
16 mm / 4" - 7"	4	10	40	
16 mm / 13"	2	10	20	
24 mm / 4" - 7"	2	8	16	
24 mm / 13"	3	8	24	
32 mm / 13"	3	7	21	
44 mm / 13"	1	5	5	
56 mm / 13"	0	4	0	

## CASSETTES

CASSETTES AVAILABLE		
REEL WIDTH	REEL DIAMETERS	
	4" - 7"	13"
8 mm	•	•
12 mm	•	•
16 mm	•	•
24 mm	•	•
32 mm		•
44 mm		•
56 mm		•

## SOFTWARE

SOFTWARE FUNCTION		
	STANDARD MODE	MYCENTER MODE
Component management	•	(2)
Stock monitoring	•	(2)
External communication protocol	•	•
User Access System	•	•
Traceability	•	•
Job preparation	•	(2)
Barcoding	•	(2)
Data Import/Export Function	•	(2)
Inventory Function	•	(2)
Component allocation	•	

(2) Handled by MYCenter software.

## ACCESSORY

DRY AIR UNIT FREY FND 3.0 F-DP	
Flow rate, max	(in) 24 m <sup>3</sup> /h, (out) 20 m <sup>3</sup> /h
Flow rate, type	3 m <sup>3</sup> /h
Air supply	class 4 (ISO 8573-1) or better
Operating pressure	5 - 10 bar
Power supply	115/230 V, 50/60 Hz, 18W
Dimension (W x D x H)	330 mm x 270 mm x 840 mm (13.0" x 10.6" x 33.1")

## MISCELLANEOUS


### INSTALLATION REQUIREMENTS

Weight	380 kg/840 lbs
Power requirements	Single phase AC 300 VA
Voltage	110 – 240 V, 50/60 Hz
Ambient temperature	+18 to +35 °C (65 to 95 °F), < 95% RH non condensing

## DIMENSIONS

in mm.

### Mycronic SMD Tower 2000



SWEDEN  
Mycronic AB  
PO Box 3141  
Nytorpsvägen 9  
SE-183 03 Täby  
Sweden  
Tel: +46 8 638 52 00  
Fax: +46 8 638 52 90

GERMANY  
Mycronic GmbH  
Tel: +49 89 4524248-0  
Fax: +49 89 4524248-80  
  
UK  
Mycronic Ltd.  
Tel: +44 1202 723 585  
Fax: +44 1202 723 269

FRANCE  
Mycronic S.A.S.  
Tel: +33 1 41 80 15 80  
Fax: +33 1 46 86 77 89  
  
NETHERLANDS  
Mycronic B.V.  
Tel: +31 402 62 06 67  
Fax: +31 402 62 06 68

USA  
Mycronic Inc.  
Tel: +1 978 948 6919  
Fax: +1 978 948 6915  
  
SOUTH KOREA  
Mycronic Co. Ltd.  
Tel: +82 31 387 5111  
Fax: +82 31 388 0087

CHINA  
Mycronic Co., Ltd.  
Tel: +86 21 3252 3785/86  
Fax: +86 21 3252 3780  
  
SINGAPORE  
Mycronic Pte Ltd.  
Tel: +65 6281 7997  
Fax: +65 6281 7667

JAPAN  
Mycronic Technologies  
Corporation  
Tel: +81 42 354 1320  
Fax: +81 42 354 1321

[www.mycronic.com](http://www.mycronic.com)

Specifications are subject to change without notice.  
Mycronic, MYDATA, MYDATA automation and MY: MY100, MY100DX, MY100SX, MY100LX, MY100e, MY100HXe, MY100DXe, MY100SXe, MY100LXe, MY200, MY200HX, MY200DX, MY200SX, MY200LX, MY500, MY600 and MYSynergy; T3, T4, T5 and T6; HYDRA Speedmount, Midas, ISiC; Agilis, Agilis Linear Magazine (ALM), Agilis Linear Magazine Flex (ALM FLEX), Agilis Stick Magazine (ASM), Mycronic Tray Exchanger (TEX), Mycronic Tape Magazine (TM), Mycronic Tray Wagon Magazine (TWM); Mycronic Dip unit (DPU); Mycronic Standard Vision System (SVS), Mycronic Dual Vision System (DVS), Mycronic Linescan Vision System (LVS), Mycronic HYDRA Vision System (HVS); Mycronic Assembly Process Management (APM) including: JPSys, TPSys, MYLabel, MYPlan, MYCenter, MYTrace, MYCam, FlowLine and Cad Conversion are registered trademarks or trademarks of Mycronic AB. Mycronic is ISO 9001:2008 certified.

# MYCRONIC